## NSN 5320-01-147-6094

Pin-rivet - Page 1 of 2

73197-hl10 manufacturers standard



View Online at https://aerobasegroup.com/nsn/5320-01-147-6094						
Thread Class:						
3a						
Thread Direction:						
Right-hand						
Identification Code Color:						
Blue						
Fastener Length:						
Between 0.627 inches and 0.647 inches						
Head Style:						
Err-090						
Head Height:						
Between 0.045 inches and 0.055 inches						
Width Between Flats:						
Between 0.079 inches and 0.081 inches						
Shank Diameter:						
Between 0.188 inches and 0.190 inches						
Shank Style:						
Pin-rivet, straight, threaded						
Head Major Diameter:						
Between 0.295 inches and 0.315 inches						
Lubrication:						
Cetyl alcohol, specification 305, hi-shear corp						
Grip Length:						
Between 0.307 inches and 0.317 inches						
Thread Size:						
0.190 inches						
Shear Strength:						
5380 double pounds per square inch						
Special Features:						
U/w collars hl70, hl79, hl82, hl94k, hl94v, hl97k, hl97v, hl379v and hl379sy						
Heat Treatment:						
As fabricated						
Material:						
Titanium alloy uns r56400						
Material Specification:						
Ams 4928 assn standard single material response or ams 4967 assn standard single material response						
Surface Treatment Specification:						
Spec 306, type 1, color blue mfr ref single treatment response						
Thread Series Designator:						
Unjf						
Specification Data:						

## NSN 5320-01-147-6094

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0