## NSN 5320-01-148-2701



Solid Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-148-2701 Fastener Length: Between 0.365 inches and 0.385 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.155 inches and 0.158 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** Between 0.2251 inches and 0.2469 inches **Head Minor Diameter:** 0.185 mils and 0.195 centimeters **Countersink Height:** 0.0372 inches **Shear Strength:** 33000 single pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Heat Treatment:** T-4 solution heat treated Material: Aluminum alloy 2017 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.