## NSN 5320-01-148-3286

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-148-3286 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 1.385 inches and 1.405 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.094 inches and 0.096 inches **Shank Diameter:** 0.249 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.390 inches and 0.395 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.000 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Hi-shear specification 306, type 1 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-148-3286

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0