NSN 5320-01-148-5940

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-148-5940

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.661 inches and 0.701 inches

Head Style:

Err-090

Head Height:

Between 0.070 inches and 0.078 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.483 inches and 0.503 inches

Lubrication:

Dry film

Grip Length:

Between 0.189 inches and 0.250 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Shear Strength:

156000 single pounds per square inch

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a



NSN 5320-01-148-5940

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

