NSN 5320-01-148-7506



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-148-7506 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.945 inches and 0.985 inches **Head Style:** Err-090 **Head Height:** Between 0.039 inches and 0.047 inches Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.245 inches and 0.257 inches Lubrication: Dry film **Grip Length:** Between 0.626 inches and 0.688 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 156000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6485 assn standard single material response or ams 6487 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas4450 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-148-7506

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0