NSN 5320-01-148-7508

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-148-7508

View Online at https://aerobasegroup.com/nsn/5320-01-148-7508
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.224 inches and 1.264 inches
Head Style:
Err-090
Head Height:
Between 0.070 inches and 0.078 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.311 inches and 0.312 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.483 inches and 0.503 inches
Lubrication:
Dry film
Grip Length:
Between 0.751 inches and 0.812 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.312 inches
Shear Strength:
156000 single pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas4450 professional/industrial association standard
Shelf Life:
N/o

N/a

NSN 5320-01-148-7508

Pin-rivet - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A528u0