# NSN 5320-01-150-0189

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-150-0189



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.828 inches and 0.848 inches

## Head Style:

Countersunk w/reverse chamfer

#### **Head Height:**

0.090 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.2021 inches and 0.2026 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.3813 inches

### Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

0.505 inches

## Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

125000 single pounds per square inch

# Countersink Angle:

100.0 degrees

## Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-150-0189

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

