NSN 5320-01-150-9511Solid Rivet - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5320-01-150-9511 |
|--|
| Fastener Length: |
| Between 0.365 inches and 0.385 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.155 inches and 0.160 inches |
| Shank Style: |
| Straight w/radius chamfered tip |
| Head Major Diameter: |
| 0.2469 inches |
| Shear Strength: |
| 49000 single pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Heat Treatment: |
| Annealed |
| Material: |
| Nickel alloy 400 |
| Material Specification: |
| Qq-n-281, class a federal specification single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Specification Data: |
| 80205-nas1200 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |