NSN 5320-01-151-1061

Blind Rivet - Page 1 of 1

A040a0

Mil-c-5541 spec.

Mil-std (military Standard):



View Online at https://aerobasegroup.com/nsn/5320-01-151-1061 **Fastener Length:** Between 0.194 inches and 0.224 inches **Head Style:** Universal **Head Height:** Between 0.054 inches and 0.064 inches **Shank Diameter:** Between 0.125 inches and 0.129 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.240 inches and 0.260 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.063 inches and 0.125 inches **Special Features:** Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply. Material: Steel comp 8740 stem **Material Specification:** Qq-a-430 federal specification single material response sleeve **Surface Treatment:** Cadmium stem and chromate stem **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: