## NSN 5320-01-151-6109

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Head Style:** 

**Head Height:** 0.1098 inches

**Thread Direction:** 

Fastener Length:

Between 1.070 inches and 1.090 inches

Countersunk w/reverse chamfer

За



View Online at https://aerobasegroup.com/nsn/5320-01-151-6109

Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2802 inches and 0.2807 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.5066 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
0.693 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
0.250 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Thread modified to mc air 0.250-20 unjf-3a
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc

## NSN 5320-01-151-6109

Pin-rivet - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0