## NSN 5320-01-151-6110

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-151-6110

#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 0.882 inches and 0.902 inches

## Head Style:

Countersunk w/reverse chamfer

#### **Head Height:**

0.1098 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2802 inches and 0.2807 inches

#### Shank Style:

Head Major Diameter:

0.5066 inches

## Lubrication:

Dry film and cetyl alcohol

## Grip Length:

0.505 inches

## Thready Qty Per Inch (tpi):

20

#### Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

## **Countersink Angle:**

100.0 degrees

## **Special Features:**

Thread modified to mc air 0.250-20 unjf-3a

## Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

## Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## **Thread Series Designator:**

Unjc



# NSN 5320-01-151-6110

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

