NSN 5320-01-152-5629

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-152-5629



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.766 inches and 0.786 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

0.0565 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2021 inches and 0.2026 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.3016 inches

Lubrication:

Dry film and cetyl alcohol

Grip Length:

0.443 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-152-5629

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

