# NSN 5320-01-153-0272

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-153-0272



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.007 inches and 1.027 inches

### Head Style:

Countersunk w/reverse chamfer

#### **Head Height:**

0.1163 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2646 inches and 0.2651 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

0.5066 inches

#### Lubrication:

Dry film and cetyl alcohol

#### Grip Length:

0.630 inches

### Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

125000 single pounds per square inch

# Countersink Angle:

100.0 degrees

## Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-153-0272

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

