# NSN 5320-01-154-0930

Pin-rivet - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5320-01-154-0930



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.947 inches and 0.967 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.567 inches

## Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A528u0