## NSN 5320-01-154-4351

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-154-4351 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.882 inches and 0.902 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** 0.1163 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2646 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** 0.505 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-154-4351

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0