

View Online at <https://aerobasegroup.com/nsn/5320-01-159-5752>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Any acceptable

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.1630 inches and 0.1650 inches

**Shank Style:**

Blind rivet, nut and bolt (assembly)

**Head Major Diameter:**

0.3304 inches

**Expansion Device:**

Threaded mandrel

**Fluid Tight Seal Type:**

O-ring under head

**Lubrication:**

Dry film and cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.562 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Seal Material:**

Rubber synthetic

**Material:**

Steel comp xm-13 expander

**Material Specification:**

Qq-s-763 federal specification single material response sleeve

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0