NSN 5320-01-160-6865

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-160-6865

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.120 inches and 1.145 inches
Head Style:
Err-090
Head Height:
Between 0.192 inches and 0.204 inches
Shank Diameter:
0.6913 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
Between 1.028 inches and 1.044 inches
Tip Diameter:
0.6861 inches
Lubrication:
Cetyl alcohol and dry film
Grip Length:
Between 0.490 inches and 0.505 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.625 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nac1720 professional/industrial association standard

NSN 5320-01-160-6865

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0