NSN 5320-01-161-9131

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

3a

View Online at https://aerobasegroup.com/nsn/5320-01-161-9131



Between 1.215 inches and 1.240 inches Head Style: Err-090 **Head Height:** Between 0.192 inches and 0.204 inches Shank Diameter: 0.7252 inches Shank Style: Pin-rivet, tapered, threaded Head Major Diameter: Between 1.061 inches and 1.077 inches **Tip Diameter:** 0.7199 inches Lubrication: Dry film and cetyl alcohol Grip Length: Between 0.490 inches and 0.505 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.625 inches Shear Strength: 125000 single pounds per square inch Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5320-01-161-9131

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

