

View Online at <https://aerobasegroup.com/nsn/5320-01-162-5763>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.208 inches and 1.228 inches

Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

Width Between Flats:

0.125 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Head Major Diameter:

Between 0.475 inches and 0.505 inches

Grip Length:

0.693 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 1 class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6758 spec.