## NSN 5320-01-162-9770

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-162-9770 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.565 inches and 1.585 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3016 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.255 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1, 294, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-162-9770

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0