NSN 5320-01-163-0179

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-163-0179

Fastener Length:
0.193 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
0.110 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.349 inches and 0.357 inches
Expansion Device:
Serrated stem-type w
Grip Length:
Between 0.080 inches and 0.125 inches
Min. Tensile Strength (psi):
635 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Ns" letters after the material code "b" indicate no preference to lock type (may be visible or internal). Rivets with no letter code (indicating
visible lock type) and rivets with the letter "h" after the material code (indicating internal lock type) are both acceptable for this item of supply.
Material:
Steel comp 8740 stem
Material Specification:
Qq-a-430 federal specification single material response sleeve
Surface Treatment:
Cadmium stem
Surface Treatment Specification:
Qq-p-416 federal specification single treatment response stem
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):
Mil-c-5541 spec.