NSN 5320-01-163-0628



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-163-0628 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.457 inches and 0.482 inches **Head Style:** Err-090 **Head Height:** Between 0.044 inches and 0.056 inches **Shank Diameter:** 0.2010 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.302 inches and 0.312 inches Tip Diameter: 0.1990 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.177 inches and 0.192 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 125000 single pounds per square inch Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1728 professional/industrial association standard

NSN 5320-01-163-0628

Pin-rivet - Page 2 of 2



| - | | | | | |
|---|----|----|----|---|---|
| • | he | 1+ | 18 | Δ | • |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0