NSN 5320-01-163-1489

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-163-1489 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.646 inches and 1.671 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Tip Diameter: Between 0.3020 inches and 0.3060 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.240 inches and 1.250 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 16600 double pounds per square inch Material: Steel comp e4340 **Material Specification:** II-s-5000 military specification 10th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-163-1489

Pin-rivet - Page 2 of 2



| Unit Of | Measure: |
|---------|----------|
| | |

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

spec.