## NSN 5320-01-163-1490

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-163-1490 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.021 inches and 2.046 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches **Tip Diameter:** Between 0.3640 inches and 0.3680 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.615 inches and 1.630 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 23900 double pounds per square inch Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-163-1490

Pin-rivet - Page 2 of 2



| U | n | it | Of | Μe | eas | ur | e: |
|---|---|----|----|----|-----|----|----|
|   |   |    |    |    |     |    |    |

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.