NSN 5320-01-163-1490

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-163-1490



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.021 inches and 2.046 inches

Head Style:

Err-090

Head Height:

Between 0.130 inches and 0.140 inches

Shank Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.565 inches and 0.600 inches

Tip Diameter:

Between 0.3640 inches and 0.3680 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.615 inches and 1.630 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

23900 double pounds per square inch

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-01-163-1490

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

