## NSN 5320-01-163-2569

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-163-2569

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.690 inches and 0.710 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.104 inches and 0.119 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.297 inches and 0.302 inches
Lubrication:
Cetyl alcohol
Grip Length:
0.375 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
100.0 degrees
Product Name:
Pin, rivet
Material:
Titanium alloy
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Per hi-shear specification 294 mfr ref single treatment response
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5320-01-163-2569

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0