

View Online at <https://aerobasegroup.com/nsn/5320-01-163-4012>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.160 inches and 1.200 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.042 inches and 0.050 inches

**Width Between Flats:**

Between 0.0791 inches and 0.0806 inches

**Shank Diameter:**

Between 0.2016 inches and 0.2026 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.298 inches and 0.312 inches

**Grip Length:**

Between 0.813 inches and 0.875 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Shear Strength:**

156000 single pounds per square inch

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and nickel

**Surface Treatment Specification:**

Ams 2416 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas4450 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0