## NSN 5320-01-165-1386

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-165-1386

| • •  |
|--|
| Fastener Length:   |
| Between 0.266 inches and 0.286 inches  |
| Head Style:  |
| Oval countersunk   |
| Shank Diameter:  |
| Between 0.139 inches and 0.143 inches  |
| Shank Style:   |
| Self-plugging mechanically locked stem                                       |
| Head Major Diameter:   |
| 0.230 inches   |
| Expansion Device:  |
| Serrated stem-type w   |
| Grip Length:   |
| Between 0.126 inches and 0.187 inches  |
| Countersink Angle:   |
| Between 98.5 degrees and 101.5 degrees                                       |
| Material:  |
| Steel comp 8740 stem   |
| Material Specification:  |
| Qq-a-430 federal specification single material response sleeve               |
| Surface Treatment:   |
| Cadmium stem and chromate stem   |
| Surface Treatment Specification:   |
| Qq-p-416 type 2 class 2 federal specification single treatment response stem |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A040a0   |
| Mil-std (military Standard):   |
| Mil-c-5541 spec.   |