## NSN 5320-01-165-1392



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-165-1392 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.385 inches and 1.405 inches **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.005 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Flat chamfer head style Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield iii fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-165-1392

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0