NSN 5320-01-165-4340

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-165-4340

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.260 inches and 1.280 inches
Head Style:
Err-090
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2490 inches and 0.2495 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
0.5066 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corporation and solid film
End Application:
W/s: aircraft, hornet f/a-18
Grip Length:
0.880 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
100.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Ti-shield iii, fscm 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-165-4340

Pin-rivet - Page 2 of 2



	She	lf	Life:	
--	-----	----	-------	--

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0