NSN 5320-01-165-4341

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-165-4341 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.447 inches and 1.467 inches **Head Style:** Err-090 Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** 1.067 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield iii, fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

NSN 5320-01-165-4341

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0