## NSN 5320-01-165-7631

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-165-7631 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.073 inches and 1.093 inches **Head Style:** Err-090 Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **End Application:** W/s: aircraft, hornet f/a-18 **Grip Length:** 0.693 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-165-7631

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0