NSN 5320-01-167-5532

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-167-5532 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.323 inches and 1.343 inches **Head Style:** Err-090 **Head Height:** Between 0.059 inches and 0.069 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.387 inches and 0.412 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.943 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield iii fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-167-5532

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0