NSN 5320-01-167-5533

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-167-5533



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.947 inches and 0.967 inches

Head Style:

Err-090

Head Height:

Between 0.080 inches and 0.090 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.415 inches and 0.440 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

End Application:

F/a-18e/f hornet aircraft; aircraft, eagle f-15; aiaircraft, hornet f/a-18

Grip Length:

0.567 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-167-5533

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

