# NSN 5320-01-168-3997

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-168-3997



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 0.565 inches and 0.585 inches

#### Head Style:

Err-090

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1890 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

0.3813 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.255 inches

## Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.190 inches

#### Shear Strength:

95000 single pounds per square inch

#### Countersink Angle:

100.0 degrees

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-168-3997

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

