NSN 5320-01-168-6386

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-168-6386

Fastener Length:

0.437 inches

Head Style:

Undersized oval countersunk

Head Height:

Between 0.003 inches and 0.005 inches

Shank Diameter:

Between 0.124 inches and 0.127 inches

Shank Style:

Straight w/radius chamfered tip

Head Major Diameter:

0.1957 inches

Head Minor Diameter:

0.134 mils and 0.144 centimeters

Countersink Height:

0.0286 inches

Shear Strength:

41000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Optional square end

Heat Treatment:

T-73 solution heat treated

Material:

Aluminum alloy 7050

Material Specification:

Qq-a-430 federal specification single material response

Surface Treatment:

Anodize or chromate

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541, cl 1a military specification 2nd treatment response

Specification Data:

80205-nas1097 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

NSN 5320-01-168-6386

Solid Rivet - Page 2 of 2

Mil-std (military Standard):

Mil-a-8625 spec.

