# NSN 5320-01-169-5590

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-169-5590

## Fastener Length:

0.312 inches

#### Head Style:

Undersized oval countersunk

## Head Height:

Between 0.003 inches and 0.005 inches

#### Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

0.1957 inches

#### Head Minor Diameter:

Between 0.134 inches and 0.144 inches

#### **Countersink Height:**

0.0286 inches

## Shear Strength:

41000 single pounds per square inch

## Countersink Angle:

100.0 degrees

## **Special Features:**

Optional squared end

## Heat Treatment:

T-73 solution heat treated

#### Material:

Aluminum alloy 7050

#### **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Chromate

#### Surface Treatment Specification:

Mil-c-5541 class 1a military specification single treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

# NSN 5320-01-169-5590

Solid Rivet - Page 2 of 2

## Mil-std (military Standard):

Mil-c-5541 spec.

