## NSN 5320-01-169-5591



Solid Rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-169-5591 Fastener Length: 0.375 inches **Head Style:** Undersized oval countersunk **Head Height:** Between 0.003 inches and 0.005 inches **Shank Diameter:** Between 0.155 inches and 0.158 inches **Shank Style:** Straight w/radius chamfered tip **Head Major Diameter:** 0.2469 inches **Head Minor Diameter:** 0.185 mils and 0.195 centimeters **Countersink Height:** 0.0372 inches **Shear Strength:** 41000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Optional squared end **Heat Treatment:** T-73 solution heat treated Material: Aluminum alloy 7050 **Material Specification:** Qq-a-430 federal specification single material response **Surface Treatment:** Chromate **Surface Treatment Specification:** Mil-c-5541 class 1a military specification single treatment response **Specification Data:** 80205-nas1097 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** n:

Demilitarizatio	r
No	

Fiig: A040a0

## NSN 5320-01-169-5591

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.