NSN 5320-01-169-5593

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-169-5593

Fastener Length:
0.375 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.003 inches and 0.005 inches
Shank Diameter:
Between 0.124 inches and 0.127 inches
Shank Style:
Straight w/radius chamfered tip
Head Major Diameter:
0.1957 inches
Head Minor Diameter:
0.134 mils and 0.144 centimeters
Countersink Height:
0.0286 inches
Shear Strength:
41000 single pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
Optional squared end
Heat Treatment:
T-73 solution heat treated
Material:
Aluminum alloy 7050
Material Specification:
Qq-a-430 federal specification single material response
Surface Treatment:
Anodize or chromate
Surface Treatment Specification:
Mil-a-8625 military specification 1st treatment response or mil-c-5541, cl 1a military specification 2nd treatment response
Specification Data:
80205-nas1097 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0

NSN 5320-01-169-5593

Solid Rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.