## NSN 5320-01-169-8286

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-169-8286 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.815 inches and 2.835 inches **Head Style:** Err-090 Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3813 inches Lubrication: Solid film or dry film and cetyl alcohol **End Application:** W/s: aircraft, hornet f/a-18 **Grip Length:** 2.505 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-169-8286

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0