

View Online at <https://aerobasegroup.com/nsn/5320-01-171-3432>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.1970 inches and 0.1990 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.3016 inches

Expansion Device:

Threaded stem

Lubrication:

Cetyl alcohol or dry film or grease film or wax

Grip Length:

Between 0.345 inches and 0.406 inches

Hardness Rating:

39.0 rockwell c nut and 46.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Mil-s-5626 military specification 1st material response nut or mil-s-6049 military specification 2nd material response nut or mil-s-6758 military specification 3rd material response nut

Surface Treatment:

Passivate sleeve or cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response bolt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.