NSN 5320-01-171-6601

Blind Rivet - Page 1 of 1



| view Online at https://aerobasegroup.com/hsh/5520-01-171-6601 |
|--|
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.197 inches and 0.199 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| 0.385 inches |
| Expansion Device: |
| Threaded stem |
| Grip Length: |
| Between 0.845 inches and 0.906 inches |
| Hardness Rating: |
| 30.0 rockwell c nut and 45.0 rockwell c nut |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5732 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Specification Data: |
| 80205-nas1672 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |