NSN 5320-01-173-3696

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-173-3696

View Online at https://aerobasegroup.com/nsn/5320-01-173-3696
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.896 inches and 0.921 inches
Head Style:
Flush countersunk
Shank Diameter:
0.3547 inches
Head Major Diameter:
0.522 inches
Tip Diameter:
0.3476 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 0.490 inches and 0.505 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.3125 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Criticality Code Justification:
Feat
Special Features:
A8-32unjc-3b thread size, 0.280 in. Length of threads along the longitudinal axis from the head end, 0.120 in. Slot length, 0.060 in. Slot width
located 0.220 in. From top of head to center of slot
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-173-3696

Pin-rivet - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0