## NSN 5320-01-175-3330

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-175-3330 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.815 inches and 1.835 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style: Head Major Diameter:** Between 0.565 inches and 0.600 inches **Grip Length:** 1.255 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Thread Size: 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** One collar included Material: Steel comp 4140 or steel comp 8740 or steel comp 4130 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response

--

Unf

N/a

Shelf Life:

**Unit Of Measure:** 

**Thread Series Designator:** 

## NSN 5320-01-175-3330

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.