NSN 5320-01-175-4682

Solid Rivet - Page 1 of 1

Mil-p-16232 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-175-4682

view Offilite at https://aerobasegroup.com/hist//5020-01-170-4002
Fastener Length:
Between 0.750 inches and 0.760 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.182 inches and 0.185 inches
Shank Style:
Straight
Head Major Diameter:
Between 0.326 inches and 0.351 inches
Hardness Rating:
60.0 rockwell b shank end
Countersink Angle:
Between 88.0 degrees and 92.0 degrees
Special Features:
Used on mach gun, cal. 50: fixed, m85
Material:
Steel
Material Specification:
Fed standard 66, comp 1005 through 1022, any cond federal standard single material response
Surface Treatment:
Phosphate manganese or phosphate zinc
Surface Treatment Specification:
Mil-p-16232, type m, class 1 military specification 1st treatment response or mil-p-16232, type z, class 1 military specification 2nd treatment
response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):