NSN 5320-01-175-6992

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-175-6992



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.863 inches and 1.883 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.4990 inches and 0.4995 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.193 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Shear Strength:

125000 single pounds per square inch

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

258 fscm 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-175-6992

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

