
# NSN 5320-01-176-0942

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.947 inches and 0.967 inches

## Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

# Width Between Flats:

Between 0.0947 inches and 0.0967 inches

### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 0.415 inches and 0.440 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

0.567 inches

# Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

# Shear Strength:

125000 single pounds per square inch

# Material:

Steel comp xm-13

# **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Passivate

# Surface Treatment Specification:

258 fscm 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-176-0942

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

