## NSN 5320-01-177-0924

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-177-0924 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.722 inches and 1.742 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.7604 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.192 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 258 fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-177-0924

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0