## NSN 5320-01-177-1682

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-177-1682

| Fastener Length:  |
|---|
| 0.636 inches  |
| Head Style:   |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)  |
| Shank Diameter:   |
| 0.140 inches  |
| Shank Style:  |
| Self-plugging Self-plugging   |
| Head Major Diameter:  |
| Between 0.221 inches and 0.229 inches   |
| Expansion Device:   |
| Serrated stem-type w  |
| Grip Length:  |
| Between 0.438 inches and 0.500 inches   |
| Min. Tensile Strength (psi):  |
| 325 pounds per square inch  |
| Shear Strength:   |
| 560 single pounds per square inch   |
| Countersink Angle:  |
| 100.0 degrees   |
| Material:   |
| Aluminum alloy  |
| Surface Treatment:  |
| Anodize expander  |
| Test Data Document:   |
| 29666-osmls100 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain       |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                         |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A040a0  |
|   |