NSN 5320-01-177-1683

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-177-1683

| Fastener Length: |
|---|
| 0.326 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| 0.173 inches |
| Head Major Diameter: |
| Between 0.282 inches and 0.290 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.125 inches and 0.188 inches |
| Min. Tensile Strength (psi): |
| 490 pounds per square inch |
| Shear Strength: |
| 855 single pounds per square inch |
| Countersink Angle: |
| 100.0 degrees |
| Special Features: |
| Oversize dia, for repair/replacement of nas1921b05-03 |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Anodize expander |
| Test Data Document: |
| 29666-osmls100 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |
| |